



GAMBRINUS BLACK SM 10

For abrasive dry food such as flour, sugar, grains, granules, pellets and animal food. Suitable for suction and delivery.

Hose construction

Tube: White NR/SBR, non-toxic. Manufactured on polished stainless steel mandrel for an ultra-smooth, bacteria free tube that does not impart taste or odor and it is resistant to abrasion

Reinforcement: Synthetic textile fabrics, embedded steel wire helix to provide suction capability and kink resistance

Cover: Black NR/SBR rubber compound, antistatic (R<10 6 /m) resistant to abrasion and weather-resistant

Temperature range

-40 °C (-40 °F) to +80 °C (+176 °F)
sterilization at 110 °C for max 30 min.



- According to FDA, BfR class 2, DM 21/03/73, EC 1935/2004
- In-plant and tank transfer, delivery and transport
- Burst Pressure Value 3:1
- Vacuum: 0.9 bar

According to
RMA steel mandrel

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	Min R mm
IH36242203/40	51	65	10	30	1.92	300
IH36242204/40	60	75	10	30	2.30	360
IH36242205/40	63.5	79	10	30	2.43	380
IH36242206/40	70	86	10	30	2.80	420
IH36242207/40	76	92	10	30	3.25	450
IH36242208/40	80	96	10	30	3.45	480
IH36242209/20	102	118	10	30	4.80	610

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses