



GASINOX /B1 /S

Hose for medium pressure.

Hose construction

Maximum flexibility corrugated tube with 1 braid
Quality of corrugated tube: AISI. 316

Temperature range

-200°C ÷ 800°C



Number	ID mm	WP bar	TP bar	BP bar	R min mm	W Kg/m
SSHCG21006	6	170	257	690	55	0,33
SSHCG21010	10	158	227	604	60	0,48
SSHCG21012	12	113	174	452	65	0,60
SSHCG21015	15	95	136	494	70	0,70
SSHCG21020	20	90	133	348	85	0,75
SSHCG21025	25	72	120	308	95	0,95
SSHCG21032	32	52	83	238	105	1,40
SSHCG21040	40	48	67	182	150	1,75
SSHCG21050	50	40	61	186	165	2,45
SSHCG21065	65	32	56	138	200	3,00
SSHCG21080	80	28	40	128	300	3,55
SSHCG21100	100	20	32	86	350	4,80
SSHCG21125	125	16	24	64	400	7,50
SSHCG21150	150	11	16	40	550	9,10
SSHCG21200	200	8	12	32	600	10,5
SSHCG21250	250	6	9	24	850	12,5

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses