



GASINOX /B2 /S

Hose for high pressure.

Hose construction

Maximum flexibility corrugated tube with 2 braids
Quality of corrugated tube: AISI. 316

Temperature range

-200°C ÷ 800°C



Number	ID mm	WP bar	TP bar	BP bar	R min mm	W Kg/m
SSHCG22006	6	305	452	1100	55	0,45
SSHCG22010	10	260	380	880	60	0,65
SSHCG20012	12	206	304	804	65	0,80
SSHCG22015	15	160	240	650	70	0,91
SSHCG22020	20	150	230	600	85	1,00
SSHCG22025	25	115	185	460	95	1,25
SSHCG22032	32	89	133	356	105	1,95
SSHCG22040	40	72	108	288	150	2,45
SSHCG22050	50	50	72	192	165	3,40
SSHCG22065	65	41	61	164	200	4,20
SSHCG22080	80	38	57	152	300	5,00
SSHCG22100	100	30	51	130	350	6,70
SSHCG22125	125	26	38	100	400	10,2
SSHCG22150	150	20	30	80	550	12,7
SSHCG22200	200	14	21	56	600	15,5
SSHCG22250	250	12	19	50	850	18,0

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses