



GASSOFLEX AAE 10

Gassoflex AAE is recommended for the delivery and/or suction of fuels, oils and lubricants in cistern trucks, railcars or fixed deposits. However, due to its aluminium wire spiral it is significantly lighter and easier to handle especially in large diameters.

Hose construction

Internal metallic helix: Aluminium (A)

External metallic helix: Aluminium (A)

Inner layer: Polypropylen (E).

Layers: Polypropylen.

Temperature range

-20 °C ÷ +100 °C



- Suction - 0,8 bar
- Working pressure 10bar
- The working pressure is based on a safety factor of 5:1

Number	ID mm	OD mm	WP bar	BP bar	Weight kg	R мин mm
AAE1010	25	-	10	50	0,37	51
AAE1012	32	-	10	50	0,48	55
AAE1015	38	-	10	50	0,65	78
AAE1020	50	-	10	50	1,00	142
AAE1025	63	-	10	50	1,45	170
AAE1030	75	-	10	50	1,70	218
AAE1040	100	-	10	50	2,97	240

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses