



## GASSOFLEX AAE 14

Gassoflex AAE is recommended for the delivery and/or suction of fuels, oils and lubricants in cistern trucks, railcars or fixed deposits. However, due to its aluminium wire spiral it is significantly lighter and easier to handle especially in large diameters.

### Hose construction

**Internal metallic helix:** Aluminium (A)

**External metallic helix:** Aluminium (A)

**Inner layer:** Polypropylen (E).

**Layers:** Polypropylen.

### Temperature range

-20 °C ÷ +100 °C



- Suction - 0,8 bar
- Working pressure 10bar
- The working pressure is based on a safety factor of 5:1

| Number  | ID mm | OD mm | WP bar | BP bar | Weight kg | R мин mm |
|---------|-------|-------|--------|--------|-----------|----------|
| AAE1410 | 25    | -     | 14     | 70     | 0,37      | 51       |
| AAE1412 | 32    | -     | 14     | 70     | 0,48      | 55       |
| AAE1415 | 38    | -     | 14     | 70     | 0,65      | 78       |
| AAE1420 | 50    | -     | 14     | 70     | 1,00      | 142      |
| AAE1425 | 63    | -     | 14     | 70     | 1,45      | 170      |
| AAE1430 | 75    | -     | 14     | 70     | 1,70      | 218      |
| AAE1440 | 100   | -     | 14     | 70     | 2,97      | 240      |

## Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5  
 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

## Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses