



GASSOFLEX GGE 14

Gassoflex GGE is recommended for use in delivery and/or suction of fuels, oils and lubricants in cistern trucks, railcars or fixed deposits.

Hose construction

Internal metallic helix: Galvanized steel (G)

External metallic helix: Galvanized steel (G)

Inner layer. Polypropylen (E).

Layers. Polypropylen.

Temperature range

-20 °C ÷ +100 °C



- Suction - 0,8 bar
- Working pressure 14bar
- The working pressure is based on a safety factor of 5:1

Number	ID mm	OD mm	WP bar	BP bar	Weight kg	R мин mm
GGE1410	25	-	14	70	0,75	68
GGE1412	32	-	14	70	0,97	74
GGE1415	38	-	14	70	1,30	105
GGE1420	50	-	14	70	2,01	190
GGE1425	63	-	14	70	2,90	225
GGE1430	75	-	14	70	3,40	290
GGE1440	100	-	14	70	5,95	320

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses