



## GASSOFLEX SGT 10

For delivery and/or suction of a wide range of highly aggressive chemical products due to its inner lining of P.T.F.E. and is normally used in applications where the external wire spiral of galvanized steel does not come in contact with the product, being a cheaper alternative. It is used in cistern trucks, railcars and fixed deposits.

### Hose construction

**Inner helix:** Stainless steel (S)

**Outer helix:** Galvanized steel (G)

**Inner layer.** P.T.F.E. (T).

**Layers.** Polypropylen.

### Temperature range

-20 °C ÷ +100 °C

### Pressure

GASSOFLEX SGT 10 – 10 bar



- Stainless steel
- The working pressure is based on a safety factor of 5:1

### Vacuum

0,8 bar

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	R min mm
SGT1010	25	-	10	50	0,85	68
SGT1012	32	-	10	50	1,07	74
SGT1015	38	-	10	50	1,50	105
SGT1020	50	-	10	50	2,00	190
SGT1025	63	-	10	50	3,05	225
SGT1030	75	-	10	50	3,55	290
SGT1040	100	-	10	50	6,40	320

## Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

## Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses