



## GENOVA GLOBAL LL

hardwall hose used for the suction delivery of unleaded gasoline and fuels with aromatic content up to 50%, suitable for use as a tank truck or tank wagon hose.  
Hose checked and approved by INERIS for use in ATEX areas

### Hose construction

**Tube:** black, smooth, NBR1 antistatic rubber.

**Reinforcement:** high strength synthetic cord plus steel helix wire.

**Cover:** black, smooth (wrapped finish), antistatic, synthetic rubber, weathering, abrasion, ozone and oil resistant.

### Hose temperature range

-30°C to +90°C



Flexible hose for the suction and delivery of unleaded gasoline and fuels, used on tank truck or tank wagon, abrasion resistant. Approved for use in ATEX areas.

Code	ID - mm	OD - mm	WP - bar	BP - bar	Weight - kg/m	BR - mm	Vacuum - bar	Lenght - m
1455141	19	32	16	64	0,76	120	0,9	120
1453823	25	38	16	64	0,94	150	0,9	120
1454650	32	45	16	64	1,14	175	0,9	120
1454455	38	52	16	64	1,45	225	0,9	120
1450026	50	65,5	16	64	2,04	275	0,9	120
1455133	63,5	78,5	16	64	2,59	300	0,9	120
1453998	75	90	16	64	3,09	350	0,9	120
1457012	100	116	16	64	4,42	450	0,9	120

## Contact us:

"DAIS GLOBAL " LTD  
3, Poruchik Nedelcho Bonchev Str., fl. 5  
1528 Sofia, Bulgaria  
Telephone: +359 2 973 27 67  
Fax: +359 2 973 26 65  
E-mail: office@daisglobal.eu

## Catalogues:

Ducting hoses  
Industrial hoses  
Fittings  
Safety couplings  
Chemical resistance table ducting hoses  
Chemical resistance table hoses