

GENOVA GLOBAL

Flexible hose for delivery of unleaded gasoline and fuels with aromatic content up to 50%, auto-extinguishing and abrasion resistant.

Hose construction

Tube: black, smooth, NBR1 antistatic rubber.
Reinforcement: high strength synthetic cord.
Cover: black, smooth (wrapped finish), conductive and auto-extinguishing synthetic rubber, weathering, abrasion, ozone and oil resistant.

Temperature range

-30°C to +90°C, with peaks to 110°C



- delivery of unleaded gasoline and fuels
- According to: EN 12115:11 (16 bar), EN 1761 (10 bar), ISO 2929 (10 bar), TRbF.
- Working pressure 16 bar

Number	ID	OD	WP	Burst pressure	Weight	Max lenght
	mm	mm	bar	bar	kg/m	m
1467700	10	21	16	64	0,32	120
1470353	13	24	16	64	0,38	120
IH36522309	19	30	16	64	0,51	120
IH36522310	25	37	16	64	0,66	120
IH36522311	32	45	16	64	0,89	120
IH36522312	38	51	16	64	1,04	120
1466321	40	53	16	64	1,08	120
IH36522313	50	66	16	64	1,73	120
IH36522314	63,5	79,5	16	64	2,06	120
IH36522315	75	91	16	64	2,39	120
1456385	80	96	16	64	2,58	120
IH36522316	100	116	16	64	2,97	120

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses