



## GST II Black 20

Designed for compressed air with traces of oil in industrial application. Also suitable in agriculture, construction, and general industry for water, mild chemicals and non aggressive fluids. Not to be used with oil or refined fuel.

### Hose construction

**Tube:** Black EPDM, antistatic rubber compound.

**Reinforcement:** Synthetic textile yarns.

**Cover:** Black, smooth EPDM rubber compound resistant to abrasion, heat and ozone

### Temperature range

-40 °C ÷ +100 °C

### According to

UNI EN ISO 1307



- Nitrosamine free
- Permanent fittings capability
- EPDM compound suitable also for oil mist
- All sizes on stock
- Burst Pressure Value 4:1

Number	I.D.	O.D.	WP	BP	W	R min
	mm	mm	bar	bar	kg	mm
IH709325300/100	6.5	14	20	60	0.16	50
IH709331300/100	8	16	20	60	0.20	65
IH709338300/100	9.5	17.5	20	60	0.23	75
IH709350304/100	13	22	20	60	0.36	105
IH709363304/100	16	27	20	60	0.52	130
IH709375304/40	19	29.5	20	60	0.56	150
IH7093100304/40	25	36.5	20	60	0.75	200

## Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

## Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses