



## GST II Red 15

In agriculture, construction, air tool lubricant systems and general industrial for air (including oil mist), mild chemicals and water. Suitable for MRO and OEM channel. Not to be used with oil or refined fuel.

### Hose construction

**Tube:** Black EPDM, antistatic rubber compound.

**Reinforcement:** Synthetic textile yarns

**Cover:** Red, smooth EPDM insulating rubber compound resistant to abrasion, heat and ozone

### Temperature range

-40 °C ÷ +100 °C

### According to

UNI EN ISO 1307



- Nitrosamine free
- Permanent fittings capability
- EPDM compound suitable also for oil mist
- Burst Pressure Value 4:1

Number	I.D.	O.D.	WP	BP	W	R min
	mm	mm	bar	bar	kg	mm
IH709225200/40	6.5	13	15	45	0.13	50
IH709231200/40	8	15	15	45	0.16	65
IH709238200/40	9.5	17	15	45	0.20	75
IH709250200/40	13	21	15	45	0.29	105
IH709263200/40	16	25	15	45	0.36	130
IH709275200/40	19	28	15	45	0.49	150
IH7092100200/40	25	36	15	45	0.69	200
IH7092125204/40	32	45	15	45	1.15	230
IH7092150204/40	38	52	15	45	2.76	250

### Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

### Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses