



## INERPRESS EN ISO 3821 N/L 20

Designed for delivery of inert gases.

### Hose constructon

**Tube:** Black, smooth SBR rubber compound, resistant to inert gases. Not suitable for LPG

**Reinforcement:** Synthetic textile yarns

**Cover:** Smooth (/L), SBR/EPDM rubber compound resistant to abrasion, ageing

### Temperature range

-25 °C (-13 °F) to +80 °C (+176 °F)



- For handling inert and noble gas
- Black cover following specs indication
- Excellent exibility
- Burst Pressure Value 3:1

**According to**  
EN ISO 3821

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	Min R mm
IH30412940/40	6.3	13.3	20	60	0.17	40
IH30413603/80	8	15	20	60	0.17	40
IH30412941/40	10	17	20	60	0.20	50

## Contact us:

"DAIS GLOBAL " LTD  
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria  
Telephone: +359 2 973 27 67  
Fax: +359 2 973 26 65  
E-mail: office@daisglobal.eu

## Catalogues:

Ducting hoses  
Industrial hoses  
Fittings  
Safety couplings  
Chemical resistance table ducting hoses  
Chemical resistance table hoses