



INTONACATRICI 40

Designed for delivery of plaster and abrasive materials such as mortar and wet cement from plastering machines or spray nozzles.

Hose construction

Tube: Black, abrasion resistant, antistatic smooth BR/NR rubber compound.

Abrasion max. 60 - 70 mm³

Reinforcement: Synthetic textile fabrics

Cover: Black, abrasion and weather-resistant, SBR rubber compound

Temperature range

-30 °C ÷ +70 °C

Tolerances

I.D. ≤ 19 mm: ± 0,79 mm
> 19 mm: ± 1,59 mm

O.D. ± 1,59 mm

L ± 1%



- Construction, general industrial
- Cover resistant to cuts, gouges, scus
- High working pressure
- Burst Pressure Value 3:1

According to
RMA steel mandrel

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	Min R mm
IH36822030/40	25	38	40	120	0.89	300
IH36822041/40	32	46	40	120	1.14	380
IH36822031/40	50	66	40	120	1.95	600
IH36822050/20	65	85	40	120	3.04	780

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses