



IVGBLUE 20

Softwall hose for the transfer of 32,5% urea aqueous solution (AUS 32) according to spec. ISO 22241, that dramatically reduces the amount of NOx in diesel transport vehicles (SCR technology), in agreement with the goals Euro IV, Euro V and Euro VI.

Hose construction

Tube: black, smooth, antistatic ($R < 1M\Omega/m$), and sulphur free EPDM rubber. No contamination of the additive as per ISO 22241-2 Method I - CERISIE analysis RP. n. 273/2014.

Reinforcement: high strength synthetic textile fabrics.

Cover: black, smooth, antistatic ($R < 1M\Omega/m$), EPDM rubber compound, ozone, heat and weather resistant.

Hose temperature range

-40°C to +100°C



Delivery of solutions based on urea.

Code	ID - mm	OD - mm	WP - bar	BP - bar	Weight - kg/m	BR - mm	Length - m
IVG2008015	8	15	20	60	0,16	50	100
IVG2010017	10	17	20	60	0,19	60	90
IVG2013020	13	20	20	60	0,23	80	60
IVG2016026	16	26	20	60	0,43	100	60
IVG2019030	19	30	20	60	0,56	115	40
IVG2025037	25	37	20	60	0,76	150	40

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses