



## JIFFY

Suitable for air, mild chemicals, oil, water, biodiesel, diesel, ethanol and gasoline to be used in air operated paint systems, air tools, transfer lines, vacuum lines. For agriculture, construction and general industrial. Do not use in pulsing applications, airbrake systems or vehicle fuel systems. Push-on couplings do not require bands, clamps or special tools for installation.

### Hose construction

**Tube:** Black NBR rubber compound, silicone free

**Reinforcement:** One textile braid

**Cover:** Black, smooth CR rubber compound  
MSHA

### Temperature range

-40°C to +100°C



- Reattachable coupling Parker Series 82 Push-Lok ®
- Kink resistant and superior coupling retention
- Flame resistant cover meets MSHA requirements
- Burst Pressure Value 4:1

**According to**  
UNI EN ISO 1307

Number	I.D.	O.D.	WP	BP	Weight	R min
	mm	mm	bar	bar	kg	mm
IH7212251BK/40	6.5	12.5	20	60	0.13	76
IH7212381BK/40	9.5	16	20	60	0.16	76
IH7212501BK/40	13	19	20	60	0.23	127
IH7212631BK/40	16	23	20	60	0.33	152
IH7212751BK/40	19	28	20	60	0.46	178

## Contact us:

"DAIS GLOBAL " LTD  
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria  
Telephone: +359 2 973 27 67  
Fax: +359 2 973 26 65  
E-mail: office@daisglobal.eu

## Catalogues:

Ducting hoses  
Industrial hoses  
Fittings  
Safety couplings  
Chemical resistance table ducting hoses  
Chemical resistance table hoses