



LPG 16

Type LPG 16 is a highly flexible standard Autogas hose for L.P. Gas dispensers. The plasticiser-free lining guarantees that no components can be washed out. Based on the Slimline petrol pump hose, LPG 16 has a black, smooth surface and a continuous, abrasion resistant laser marking as per example above.

Hose construction

Lining: NBR, black, seamlessly extruded, electrically conductive low diffusion, plasticiser-free

Reinforcements: low tensile textile braids with crossed tin-plated copper strands electrically connectable

Cover: CR, black, smooth, perforated, electrically conductive, highly abrasion resistant, highly ageing resistant.

Temperature range°

-40°C to +70°C



- Highly flexible and long-lasting construction.
- For propane, butane and other L.P. gases.
- Burst pressure > 100 bar.

According to
EN1762

Number	ID mm	OD mm	WP bar	BP bar	Weight kg	R мин mm
LPG016/40	16	26	25	100	0,5	90

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5
1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses