

LPG/CORD/1762

Flexible hose for the delivery of liquefied petroleum gas, LPG and natural gas, with pin pricked cover. According to EN 1762:2017.

Hose construction

Tube: extruded, black, smooth, synthetic rubber.

Reinforcement: high strength synthetic cord.

Cover: black, smooth (wrapped finish), synthetic rubber, weathering and ozone resistant. Pin pricked cover to allow gas permeation.

Temperature range

-30°C to +100°C



- delivery of liquefied petroleum gas
- electrical resistance below $1 \times 10^6 \Omega$ on service length assured through the rubber of cover (type Ω).
- Working pressure 25bar

Number	ID	OD	WP	Burst pressure	Weight	Bending radius	Max length
	mm	mm	bar	bar	kg/m	mm	m
IH30515071	13	24	25	100	0,39	160	60
IH36520580	19	32	25	100	0,62	180	60
IH36520581	25	38	25	100	0,77	200	60
IH36520582	32	46	25	100	1,04	250	60
IH36520583	38	54	25	100	1,32	320	60
IH36520584	50	67	25	100	1,76	400	60
IH36520587	75	93	25	100	2,70	650	60
1425730	102	124	25	100	4,43	800	60

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses