

MANITOBA

Softwall steam hose, textile reinforced, recommended for use with saturated steam at a maximum working pressure of 6 bar (90 psi). For longer life drain after use.

Hose construction

Tube: black, smooth, EPDM rubber, resistant to saturated steam.

Reinforcement: high strength synthetic cord.

Cover: black, smooth (wrapped finish), EPDM rubber, resistant to high temperatures, weathering and ozone.



- Flexible hose for delivery of saturated steam at 165°C (+329°F) and a maximum working pressure of 6 bar (90 psi), textile reinforced.
- Working pressure 6 bar

Temperature range

-40°C to +165°C

Number	ID mm	OD mm	WP bar	Burst pressure bar	Weight kg/m	Max lenght m
IH36800098	10	21	6	60	0,28	120
1023829	12	23	6	60	0,32	120
IH36800088	13	23	6	60	0,29	120
IH36800089	16	27	6	60	0,39	120
1023926	19	29	6	60	0,39	120
IH36800090	19	31	6	60	0,50	120
IH36800091	25	37	6	60	0,59	120
1024043	30	45	6	60	0,87	120
IH36800092	32	46,5	6	60	0,89	120
IH36800093	38	54	6	60	1,17	120
IH36800096	51	68	6	60	1,63	120

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses