



MINIERA 10

Suitable for compressed air tools (with minimal oil traces) in factories and designed for quarries, building and mining industries.

Hose construction

Tube: Black, oil mist resistant, smooth SBR nitrosamine free rubber compound

Reinforcement: Synthetic textile fabrics

Cover: Black, abrasion, ageing and weather-resistant SBR nitrosamine free rubber compound

Temperature range

-30 °C ÷ +80 °C



- Also suitable for water and air in general service applications
- Nitrosamine free compounds
- Burst Pressure Value 3:1

According to
RMA steel mandrel

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	R мин mm
IH36342181/40	25	35	10	30	0,70	250
IH36342182/40	30	40	10	30	0,81	300
IH36342184/40	35	45	10	30	0,92	350
IH36342185/40	40	50	10	30	1,02	400
IH36342186/40	45	55	10	30	1,14	450
IH36342187/40	50	60	10	30	1,25	500
IH36342188/40	60	70	10	30	1,47	600
IH36342189/20	70	80	10	30	1,68	700
IH36342190/40	75	86	10	30	1,99	750
IH36342190/20	75	86	10	30	1,99	750
IH36342191/20	100	112	10	30	2,86	1000
IH36342194/20	102	114	10	30	2,99	1020

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses