



MINIERA 20

Suitable for compressed air tools (with minimal oil traces) in factories and designed for quarries, building and mining industries.

Hose construction

Tube: Black, oil mist resistant, smooth SBR nitrosamine free rubber compound

Reinforcement: Synthetic textile fabrics

Cover: Black, abrasion, ageing and weather-resistant SBR nitrosamine free rubber compound

Temperature range

-30 °C ÷ +80 °C



- Also suitable for water and air in general service applications
- Nitrosamine free compounds
- Burst Pressure Value 3:1

According to
RMA steel mandrel

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	R мин mm
IH36341113/40	19	30	20	60	0,62	190
IH36341110/40	25	37	20	60	0,81	250
IH36341149/40	30	42	20	60	1,39	300
IH36341111/40	32	46	20	60	1,39	300
IH36341121/40	38	52	20	60	1,43	380
IH36341120/40	40	56	20	60	1,73	400
IH36341109/40	45	61	20	60	1,91	450
IH36341114/40	50	66	20	60	2,08	500
IH36341116/40	60	76	20	60	2,38	600
IH36341117/20	75	91	20	60	2,89	750
IH36341119/20	100	118	20	60	4,23	1000

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses