

MONOFLEX

Designed for standard duty suction and delivery of liquids compatible with PVC in agriculture, industrial, irrigation and water supply applications.

Hose construction

Flexible hose made out of soft food-grade PVC wall in accordance with the modified EU regulation 10/2011, reinforced with shock resistant PVC spiral.

Temperature range

-23°C to + 140°C



- Suction and delivery of liquids
- According to 10/2011
- Working pressure 2-8bar
- Vacuum 0.6 – 0.8bar

Number	ID mm	OD mm	Weight kg/m	Bending radius mm	Налягане bar	Vacuum bar	Размер m
IH35600016	16	22,3	0,190	64	8	0,80	25/50
IH35602019	20	26,3	0,245	80	8	0,80	25/50
IH35600025	25	31,4	0,310	100	7	0,80	25/50
IH35600030	30	36,6	0,400	120	6	0,80	25/50
IH35602032	32	38,8	0,430	128	6	0,80	25/50
IH35600035	35	42,1	0,470	140	6	0,80	25/50
IH35602038	38	45,7	0,530	152	6	0,80	25/50
IH35600040	40	47,8	0,560	160	6	0,80	25/50
IH35600045	45	53,3	0,670	180	5	0,80	25
IH35600050	51	59,7	0,800	200	5	0,80	25/50
IH35600055	55	63,9	0,880	220	5	0,76	25
IH35600060	60	69,2	0,980	240	5	0,76	25
	63	72,5	1,050	252	5	0,76	25
IH35600070	70	80,1	1,150	280	4	0,76	25
IH35602075	76	86,3	1,385	300	4	0,76	25
IH35600080	80	91,3	1,560	320	4	0,76	25
IH35602090	90	101,9	1,800	360	4	0,76	25
IH35600100	102	115	2,160	400	3	0,70	25
	105	118,2	2,160	420	3	0,65	25
IH35602110	110	123,0	2,400	440	3	0,65	25
IH35600120	120	133,6	2,800	480	3	0,60	25
IH35600150	152	166,0	4,250	600	3	0,60	25
	160	175,9	4,400	640	3	0,60	10
IH35600200	203	223,0	6,400	950	2	0,60	10

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses