



MULTIFORM 10

Flexible hot water discharge hose with 10 bar (150 psi) working pressure, weathering and ageing resistant.

Hose construction

Tube: black, seamless EPDM rubber compound.
Reinforcement: high strength synthetic fabrics.
Cover: black, seamless, ageing, ozone, weathering-resistant, EPDM rubber compound.

Hose temperature range

-40°C to +120°C



Designed to convey hot water, fluids even slightly acidic and non aggressive in chemical industries

Code	ID - mm	OD - mm	WP - bar	BP - bar	Weight - kg/m	BR - mm	Length - m
1447521	5	10,5	10	30	0,08	30	100
1447530	8	15	10	30	0,15	50	100
1447548	10	17	10	30	0,17	60	100
1447840	12	19	10	30	0,21	70	100
1447564	13	19	10	30	0,18	80	100
1447572	15	23	10	30	0,28	90	60
1447580	16	23	10	30	0,25	100	60
1447661	19	26	10	30	0,31	110	60

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses