




## NEO 2

Suction and blast hose, especially suitable:

- as conductor of hot and cold air
- for granulate dryers in the plastics industry
- for printing machines, blowers and compressors
- for exhaust gas technique, engine construction, engine warming, aircraft construction and military construction

### Hose construction

1. spring steel wire integrated in wall
2. fabric-reinforced tape wall: Neopren coated glass fabric
3. cord as reinforcement



- single-layer
- very good heat resistance
- leak-proof
- highly flexible
- fibre reinforced
- small bending radius

### Temperature range

-35°C ÷ +135°C, with peaks up to +150°C

No	I.D. mm	O.D. mm	Pressure bar	Vacuum bar	Bend radius mm	Weight kg/m	Max length m
390-0013-2005	13	16	3,000	0,740	16	0,070	-
390-0019-2005	19	22	3,000	0,730	22	0,110	4
390-0022-2005	22	25	3,000	0,720	25	0,170	4
390-0025-2005	25	30	2,800	0,710	30	0,190	4
390-0032-2005	32	36	2,700	0,650	36	0,280	4
390-0038-2005	38	43	2,600	0,600	43	0,310	4
390-0041-2005	41	46	2,600	0,590	46	0,315	-
390-0044-2005	44	49	2,600	0,580	49	0,320	4
390-0045-2005	45	50	2,600	0,550	50	0,340	-
390-0051-2005	51	56	2,600	0,520	56	0,360	4
390-0057-2005	57	62	2,500	0,480	62	0,430	4
390-0060-2005	60	65	2,500	0,470	65	0,460	-
390-0063-2005	63	68	2,400	0,460	68	0,490	4
390-0070-2005	70	75	2,100	0,440	75	0,540	4
390-0076-2005	76	81	2,100	0,430	81	0,580	4
390-0080-2005	80	85	2,100	0,420	85	0,610	4
390-0083-2005	83	88	2,100	0,410	88	0,630	4
390-0089-2005	89	94	2,000	0,400	94	0,690	4
390-0095-2005	95	100	1,900	0,370	100	0,730	4
390-0102-2005	102	107	1,900	0,350	107	0,770	4
390-0108-2005	108	114	1,800	0,330	114	0,810	4
390-0114-2005	114	120	1,500	0,300	120	0,850	4
390-0121-2005	121	127	1,500	0,240	127	0,890	4

### Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5  
 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

### Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses



No	I.D. mm	O.D. mm	Pressure bar	Vacuum bar	Bend radius mm	Weight kg/m	Max length m
<b>390-0127-2005</b>	127	133	1,400	0,230	133	0,930	<b>4</b>
<b>390-0140-2005</b>	140	146	1,300	0,200	146	1,000	<b>4</b>
<b>390-0152-2005</b>	152	158	1,200	0,170	158	1,200	<b>4</b>
<b>390-0160-2005</b>	160	166	1,100	0,160	166	1,280	-
<b>390-0165-2005</b>	165	171	1,100	0,140	171	1,380	-
<b>390-0178-2005</b>	178	184	1,000	0,120	184	1,430	<b>4</b>
<b>390-0203-2005</b>	203	209	0,700	0,090	209	1,650	<b>4</b>
<b>390-0254-2005</b>	254	260	0,500	0,070	260	2,090	<b>4</b>
<b>390-0305-2005</b>	305	311	0,500	0,070	311	2,610	<b>4</b>

## Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5  
 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

## Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses