



## NORFLEX® PUR 441 MHF




Pressure hose, especially suitable:

- for compressed air
- for abrasive solids such as dust, powder, fibres and chips
- for gaseous and liquid media

### Hose construction

1. fabric reinforced wall
2. smooth interior and exterior wall: special premium ether-polyurethane (Pre-PUR®)



- highly flexible
- highly abrasion-proof
- smooth interior and exterior
- high tensile strength and tear resistant
- fabric reinforced

### According to

- FDA 21 CFR177.2600 and 178.2010, EU Directive 2002/72/EC, incl. amending Directives 975/2009 and Regulation No. 10/2011

### Temperature range

-40°C ÷ +90°C, with peaks up to +125°C.

No	I.D. mm	Wall Thickness mm	O.D. mm	Pressure bar	Bending radius mm	Weight kg/m	Max length m
441-9029-0000	2,9	1,4	5,7	20	15	0,022	50
441-9040-0000	4	2	8	20	15	0,045	50
441-9060-0000	6	2	10	16	25	0,060	50
441-9060-2175	6		12	20	25	0,100	
441-9065-0000	6,5	1.75	10	16	25	0,054	
441-9070-0000	7	1,5	10	14	30	0,047	
441-9080-0000	8	2	12	16	30	0,075	50
441-9085-0000	8,5	2	12,5	16	40	0,078	
441-9095-0000	9,5	2	13,5	14	50	0,086	
441-9100-0000	10	2,25	14,5	12	60	0,103	50
441-9110-0000	11	2,5	16	12	60	0,126	
441-9130-0000	13	3	19	10	85	0,179	50
441-9190-0000	19	3	25	8	125	0,248	50

### Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5  
 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

### Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses