




NORPLAST® PUR-CU 386



Abrasion-proof suction and transport hose;
Heavy, smooth interior, grounding wire

Hose construction

hard plastic spiral integrated in wall
spiral: rigid PVC
smooth interior
wall: interior polyurethane layer, exterior soft PVC
metallic grounding wire



- abrasion-proof inside layer
- smooth interior
- increased pressure and vacuum resistance
- high axial strength
- good resistance to chemicals

Temperature range

-20°C ÷ +70 °C, with peaks up to +80°C

No	I.D. mm	O.D. mm	Pressure bar	Vacuum bar	Bend radius mm	Weight kg/m	Max length m
386-0032-0000	32	39	5,000	0,700	154	0,450	-
386-0038-0000	38	46	5,000	0,700	182	0,590	30
386-0040-0000	40	48	5,000	0,700	195	0,620	30
386-0045-0000	45	53	5,000	0,700	215	0,750	30
386-0050-0000	50	59	5,000	0,700	235	0,880	30
386-0060-0000	60	69	5,000	0,700	275	1,060	30
386-0063-0000	63	72	5,000	0,700	290	1,130	30
386-0065-0000	65	74	5,000	0,700	300	1,170	-
386-0070-0000	70	79	5,000	0,700	320	1,280	30
386-0076-0000	76	85	5,000	0,700	340	1,460	30
386-0080-0000	80	90	4,000	0,700	365	1,630	30
386-0090-0000	90	100	4,000	0,700	420	1,940	30
386-0100-0000	100	110	4,000	0,700	470	2,290	-
386-0102-0000	102	112	4,000	0,700	475	2,310	30

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5
1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses