




NORPLAST® PVC 131



For electrical installations, installation in switchboard plant, switch cabinets and mechanical engineering; as suction and pressure hose for gaseous and liquid media

Hose construction

NORPLAST full plastic conduit; hard plastic spiral integrated in the wall; wall: high grade soft PVC; spiral: rigid PVC



- smooth interior and exterior (easy retraction of cables, easy cleaning of exterior surface)
- flexible
- gas and liquid tight
- good resistance to alkalis and acids
- good resistance to chemicals
- good resistance to UV and ozone
- insulating

Temperature range

-20 °C to +70 °C (short time +80 °C).

Number	I.D. mm	O.D. mm	connector mm	W kg	Мин R mm
131-3014-9000	10	14	14	0,10	56
131-3017-9000	13	17	17	0,12	68
131-3019-9000	15	19	19	0,14	76
131-3021-9000	16	21	21	0,16	84
131-3027-9000	22	27	27	0,25	108
131-3036-9000	30	36	36	0,40	144
131-3045-9000	38	45	45	0,52	180
131-3052-9000	45	52	52	0,66	208
131-3056-9000	49	56	56	0,70	224

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses