



OILPRESS N/L 20

Suitable for multi-purpose applications requiring transfer of many types of fluids and for petroleum products with aromatic content not exceeding 50 %.

Hose construction

Tube: Smooth, black, oil and fuel resistant NBR rubber compound, suitable for petroleum products with aromatic content not exceeding 50 %

Reinforcement: Synthetic textile yarns

Cover: Smooth, black, self-extinguishing, antistatic ($R < 1 \text{ M/m}$) heat, oil, abrasion and weather resistant CR rubber compound

Temperature range

-30°C to +100°C with peaks to +120°C



- Agriculture, construction and general industrial
- Suitable for many different fuels included Biodiesel B100
- Two different Working Pressure lines
- Wide range temperature
- Burst Pressure Value 3:1

According to
UNI EN ISO 1307

Number	I.D.	O.D.	WP	BP	W	R min
	mm	mm	bar	bar	kg	mm
OILPRESS N/L 20						
IH30832000/40	6	12	20	60	0.12	25
IH30832001/40	8	14	20	60	0.15	35
IH30832002/40	10	17	20	60	0.21	40
IH30832003/40	13	20	20	60	0.26	55
IH30832004/40	16	23	20	60	0.31	65
IH30832005/40	19	28	20	60	0.47	80
IH30832006/40	25	36	20	60	0.74	100

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses