



## OILPRESS N/L 30

Suitable for multi-purpose applications requiring transfer of many types of fluids and for petroleum products with aromatic content not exceeding 50 %.

### Hose construction

**Tube:** Smooth, black, oil and fuel resistant NBR rubber compound, suitable for petroleum products with aromatic content not exceeding 50 %

**Reinforcement:** Synthetic textile yarns

**Cover:** Smooth, black, self-extinguishing, antistatic (R < 1 M/m) heat, oil, abrasion and weather resistant CR rubber compound

### Temperature range

-30°C to +100°C with peaks to +120°C



- Agriculture, construction and general industrial
- Suitable for many different fuels included Biodiesel B100
- Two different Working Pressure lines
- Wide range temperature
- Burst Pressure Value 3:1

**According to**  
UNI EN ISO 1307

Number	I.D.	O.D.	WP	BP	W	R min
	mm	mm	bar	bar	kg	mm
<b>OILPRESS N/L 30</b>						
<b>IH30832031/40</b>	6	14	30	90	0.18	25
<b>IH30832032/40</b>	8	16	30	90	0.21	30
<b>IH30832038/40</b>	9	17	30	90	0.24	35
<b>IH30832033/40</b>	10	18	30	90	0.25	40
<b>IH30832034/40</b>	13	23	30	90	0.40	55
<b>IH30832035/40</b>	16	27	30	90	0.47	65
<b>IH30832036/40</b>	19	30	30	90	0.60	80
<b>IH30832037/40</b>	25	37	30	90	0.83	100

### Contact us:

"DAIS GLOBAL " LTD  
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria  
Telephone: +359 2 973 27 67  
Fax: +359 2 973 26 65  
E-mail: office@daisglobal.eu

### Catalogues:

Ducting hoses  
Industrial hoses  
Fittings  
Safety couplings  
Chemical resistance table ducting hoses  
Chemical resistance table hoses