

## ORLANDO

Softwall hose designed to handle a wide range of chemical products, not strong oxidizing acids, bases, alcohols, aldehydes, ketones, hot water and hot air. It is specially recommended to convey industrial waters and for use in water purification systems.

### Hose construction

**Tube:** black, smooth, EPDM rubber. Chemical resistance according to IVG chemical resistance chart. For temperature exceeding 50°C contact IVG.

**Reinforcement:** high strength synthetic cord.

**Cover:** black, smooth (wrapped finish), EPDM rubber, resistant to chemical products, abrasion, weathering and ozone.

### Temperature range

-40°C to +100°C



- Flexible hose for chemical product delivery, with EPDM rubber and according to EN 12115.
- Working pressure 6bar
- Ω/T, electrically conductive hose. Electrical resistance for lengths equal or lower than 40m.

Number	ID mm	OD mm	WP bar	Burst pressure bar	Weight kg/m	Max lenght m
<b>IH30351273</b>	19	30	16	64	0,47	120
<b>IH30351274</b>	25	37	16	64	0,64	120
<b>IH36351270</b>	32	44	16	64	0,75	120
<b>IH36351271</b>	38	51	16	64	0,97	120
<b>IH36351272</b>	51	67	16	64	1,63	120
<b>1200745</b>	63,5	81	16	64	2,13	120
<b>1200502</b>	76	93	16	64	2,50	120
<b>1469096</b>	102	120	16	64	3,33	120

### Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

### Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses