



PERFORMER AD10T

Pneumatic or hydraulic suction or discharge of abrasive materials with high temperature.

Hose construction

Tube: EPDM, black, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: weather resistant EPDM, black, corrugated, fabric impression.

Electrical properties: conductive tube and cover.

Temperature range

-30°C to + 100°C, peaks up to + 110°C.

Couplings/Fittings

Hoses can be fitted with:

- 2 END-FLEX®,
- 1 cuff + 1 END-FLEX® flange,
- 2 enlarged or smooth cuffs.

Hoses fitted with END-FLEX® flanges are allowed to work with pressure and vacuum mentioned in the table.



- Excellent resistance to abrasion at high temperature.
- Low installation cost.
- Static conductivity ensured by the helix and by the antistatic tube.
- Suppression of pressure surges.
- Reduction in head loss.
- Damping of vibrations and noise.
- Many types of fittings possible.
- Excellent weather resistance.
- Vacuum 0.9bar

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	Min R mm
AD10H-25/20	25	53	10	30	2.1	125
AD10H-32/20	32	60	10	30	2.5	160
AD10H-40/20	40	73	10	30	3.4	200
AD10H-50/20	50	83	10	30	4	250
AD10H-65/20	65	98	10	30	4.8	325
AD10H-75/20	75	108	10	30	5.4	375
AD10H-80/20	80	113	10	30	5.7	400
AD10H-100/20	100	133	10	30	7	500
AD10H-125/20	125	158	10	30	8.2	750
AD10H-150/20	150	183	10	30	9.9	1050
AD10H-175/10	175	208	10	30	11.3	1300
AD10H-200/12	200	234.5	10	30	13.9	1600
AD10H-250/12	250	285.5	10	30	17.6	2000
AD10H-300/12	300	340.5	10	30	25	2500
AD10H-350/12	350	391	10	30	30.7	3000
AD10H-400/12	400	441	10	30	36.2	4000

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses