



PERFORMER GL AD10T

Pneumatic or hydraulic suction or discharge of abrasive materials with high temperature.

Hose construction

Tube: EPDM, black, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: weather resistant EPDM, black, corrugated, fabric impression.

Electrical properties: conductive tube and cover (helix must be connected with couplings).

Temperature range

-30°C to + 100°C, peaks up to + 110°C

Couplings/Fittings

Hoses are fitted with BLOC-END® and must be used to the following maximum working pressure:

ID ≤ 150 mm: WP = 10 bar,

ID > 150 mm: WP = 5 bar



- Excellent resistance to abrasion at high temperature.
- Hose can be supplied cut to length for on-site coupling.
- Light weight and low bending radius.
- Electrical conductivity ensured by the tube and the helix.
- Suppression of pressure surges.
- Reduction in pressure head loss.
- Damping of vibrations and noise.
- Excellent weather resistance.
- Vacuum 0.9bar

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	Min R mm
TL0127950/20	25	53	10	30	2.4	125
TL0127951/20	32	60	10	30	2.8	160
TL0127952/20	40	73	10	30	4.1	200
TL0094968/20	50	83	10	30	4.4	250
TL0094233/20	65	98	10	30	4.9	325
TL0094969/20	80	113	10	30	5.6	400
TL0094290/20	100	133	10	30	7.1	500
TL0128405/20	125	158	10	30	9	750
TL0094459/20	150	183	10	30	10.2	1050
TL0126597/12	200	234.5	10	30	14.3	1600
TL0126600/12	250	285.5	10	30	17.5	2000
TL0126603/12	300	340.5	10	30	25.2	2500

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses