



PRESCORD N/R 10

Suitable for discharge of water and nonaggressive liquids in many industrial and agricultural applications.

Hose construction

Tube: Black, smooth SBR nitrosamine free rubber compound

Reinforcement: Synthetic textile yarns

Cover: Black (N), ribbed (/R), abrasion, ageing and weather-resistant, SBR/EPDM nitrosamine free rubber compound

Temperature range

-30 °C ÷ +80 °C



- Resistant to Ozone and weathering
- Nitrosamine free
- Ribbed cover for better exibility and grip
- Burst Pressure Value 3:1

According to
UNI EN ISO 1307/97

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	Min R mm
IH30116062/100	8	15	10	30	0,19	50
IH30116063/100	10	17	10	30	0,22	60
IH30112103/100	12	19	10	30	0,26	70
IH30112104/100	15	23	10	30	0,36	90
IH30112136/50	18	26	10	30	0,42	110
IH30112138/50	20	30	10	30	0,59	120
IH30112134/50	25	35	10	30	0,71	150

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses