



PROPANPRESS EN ISO 3821 N/L 20

Suitable for LPG in industrial applications.

Hose constructon

Tube: Black, LPG resistant smooth NBR rubber compound

Reinforcement: Synthetic textile yarns

Cover: Orange, smooth PVC/NBR rubber compound resistant to ageing and weathering, pin-pricked cover to prevent blisters during use

Temperature range

-30 °C (-22 °F) to +70 °C (+158 °F)



- Pin-pricked cover
- Low permeation
- Orange cover following specs indication
- Flexible hose for easy handling
- Burst Pressure Value 3:1

According to
EN ISO 3821

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	Min R mm
IH30413456/100	6.3	13.3	20	60	0.16	50
IH30413457/100	8	15	20	60	0.18	65
IH30413459/100	8.5	16	20	60	0.21	70
IH30413458/100	10	17	20	60	0.22	80

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses