



PROTAPE® PUR 330 MHF




Abrasion-proof suction and blast hose, especially suitable:

- for abrasive solids such as dust, powder, fibres and chips
- for gaseous media such as oil vapors and welding smoke
- for de-dusting and suction plants

Hose construction

spring steel wire integrated in wall thickness 0.6 mm approx. PROTAPE®



Temperature range

-40 °C ÷ +90 °C; with peaks up to +125 °C



- microbe and hydrolysis resistant
- good resistance to mineral oils and gasoline
- good resistance to chemicals
- good resistance to UV and ozone

According to

- German TRBS 2153 (formerly BGR 132): capable of electro-static discharge by grounding, recommended for many applications with the exception of inflammable bulk materials

| No | I.D. mm | O.D. mm | Pressure bar | Vacuum bar | Радиус на огъване mm | Weight kg/m | Max length m |
|---------------|---------|---------|--------------|------------|----------------------|-------------|--------------|
| 330-0025-0000 | 25 | 32 | 1,600 | 0,360 | 32 | 0,170 | 10 |
| 330-0030-0000 | 30 | 37 | 1,345 | 0,340 | 37 | 0,200 | 10 |
| 330-0032-0000 | 32 | 39 | 1,260 | 0,340 | 39 | 0,210 | 10 15 |
| 330-0038-0000 | 38 | 45 | 1,060 | 0,320 | 45 | 0,250 | 10 15 |
| 330-0040-0000 | 40 | 47 | 1,015 | 0,300 | 47 | 0,280 | 10 15 |
| 330-0045-0000 | 45 | 52 | 0,900 | 0,285 | 52 | 0,310 | - |
| 330-0050-0000 | 50 | 58 | 0,815 | 0,260 | 58 | 0,360 | 10 15 |
| 330-0051-0000 | 51 | 59 | 0,800 | 0,260 | 59 | 0,370 | 10 |
| 330-0060-0000 | 60 | 68 | 0,680 | 0,210 | 68 | 0,430 | 10 15 |
| 330-0063-0000 | 63 | 71 | 0,645 | 0,195 | 71 | 0,450 | 10 |
| 330-0065-0000 | 65 | 73 | 0,630 | 0,180 | 73 | 0,470 | 10 |
| 330-0070-0000 | 70 | 78 | 0,585 | 0,150 | 78 | 0,500 | 10 15 |
| 330-0075-0000 | 75 | 83 | 0,545 | 0,140 | 83 | 0,530 | 10 |
| 330-0076-0000 | 76 | 84 | 0,540 | 0,140 | 84 | 0,540 | - |
| 330-0090-0000 | 90 | 98 | 0,455 | 0,115 | 98 | 0,630 | 10 |
| 330-0080-0000 | 80 | 88 | 0,510 | 0,130 | 88 | 0,570 | 10 15 |
| 330-0100-0000 | 100 | 108 | 0,410 | 0,090 | 108 | 0,660 | 10 |
| 330-0102-0000 | 102 | 110 | 0,400 | 0,090 | 110 | 0,680 | 10 |
| 330-0110-0000 | 110 | 118 | 0,375 | 0,080 | 118 | 0,730 | 10 |
| 330-0115-0000 | 115 | 123 | 0,355 | 0,080 | 123 | 0,760 | 10 |
| 330-0120-0000 | 120 | 128 | 0,340 | 0,075 | 128 | 0,790 | 10 |
| 330-0125-0000 | 125 | 133 | 0,330 | 0,060 | 133 | 0,820 | 10 15 |
| 330-0127-0000 | 127 | 135 | 0,325 | 0,060 | 135 | 0,830 | 10 |
| 330-0130-0000 | 130 | 138 | 0,315 | 0,060 | 138 | 0,850 | 10 |
| 330-0140-0000 | 140 | 148 | 0,295 | 0,060 | 148 | 0,920 | 10 |
| 330-0150-0000 | 150 | 158 | 0,275 | 0,055 | 158 | 0,980 | 10 15 |

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses



| No | I.D. mm | O.D. mm | Pressure bar | Vacuum bar | Радиус на огъване mm | Weight kg/m | Max length m |
|----------------------|---------|---------|--------------|------------|----------------------|-------------|--------------|
| 330-0152-0000 | 152 | 160 | 0,270 | 0,055 | 160 | 0,990 | 10 |
| 330-0160-0000 | 160 | 168 | 0,255 | 0,050 | 168 | 1,040 | 10 |
| 330-0170-0000 | 170 | 178 | 0,240 | 0,045 | 178 | 1,110 | 10 |
| 330-0175-0000 | 175 | 183 | 0,235 | 0,040 | 183 | 1,140 | 10 |
| 330-0178-0000 | 178 | 186 | 0,230 | 0,040 | 186 | 1,160 | - |
| 330-0180-0000 | 180 | 188 | 0,230 | 0,040 | 188 | 1,170 | 10 |
| 330-0200-0000 | 200 | 208 | 0,205 | 0,040 | 208 | 1,540 | 10 |
| 330-0203-0000 | 203 | 211 | 0,205 | 0,040 | 211 | 1,570 | 10 |
| 330-0225-0000 | 225 | 233 | 0,180 | 0,030 | 233 | 1,750 | 10 |
| 330-0228-0000 | 228 | 236 | 0,180 | 0,028 | 236 | 1,770 | - |
| 330-0250-0000 | 250 | 258 | 0,165 | 0,015 | 258 | 1,900 | 10 |
| 330-0254-0000 | 254 | 262 | 0,165 | 0,015 | 262 | 1,940 | - |
| 330-0275-0000 | 275 | 283 | 0,150 | 0,015 | 283 | 2,110 | - |
| 330-0280-0000 | 280 | 288 | 0,145 | 0,015 | 288 | 2,150 | - |
| 330-0300-0000 | 300 | 309 | 0,135 | 0,015 | 309 | 2,530 | 10 |
| 330-0305-0000 | 305 | 314 | 0,135 | 0,015 | 314 | 2,570 | - |
| 330-0315-0000 | 315 | 324 | 0,130 | 0,010 | 324 | 2,650 | - |
| 330-0325-0000 | 325 | 334 | 0,125 | 0,010 | 334 | 2,740 | - |
| 330-0350-0000 | 350 | 359 | 0,115 | 0,010 | 359 | 2,950 | 10 |
| 330-0400-0000 | 400 | 409 | 0,105 | 0,010 | 409 | 3,360 | 10 |
| 330-0450-0000 | 450 | 459 | 0,090 | 0,006 | 459 | 3,770 | - |
| 330-0500-0000 | 500 | 510 | 0,080 | 0,005 | 510 | 5,160 | - |

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses