



## PROTAPE® PUR 335 MHF FLAT




Special and abrasion-proof hose, especially suitable:

- for screening machines, vibrating screening machines and tumbler screening machines
- as bellows and compensator
- for the food and pharmaceutical industry

### Hose construction

extruded tape  
wall thickness 1.0 mm approx.  
wall: special premium ether-polyurethane (Pre-PUR®)



smooth interior

### Temperature range

-40°C ÷ +140°C with peaks up to 150°C



- vibration resistant
- highly flexible
- abrasion-proof
- smooth interior
- optimized flow properties

### According to

- approved by an independent testing laboratory for the complete hose acc. to EU Directive 2002 /72/EC, incl. amending Directive 975/2009 and Regulation No. 10/2011

No	I.D. mm	O.D. mm	Pressure bar	Weight kg/m	Max length m
335-0080-0000	80	85	0,510	0,470	5
335-0085-0000	85	90	0,480	0,500	5
335-0090-0000	90	95	0,455	0,540	-
335-0100-0000	100	105	0,410	0,590	5
335-0110-0000	110	115	0,375	0,650	5
335-0115-0000	115	120	0,355	0,670	-
335-0120-0000	120	125	0,340	0,700	5
335-0125-0000	125	130	0,330	0,730	5
335-0130-0000	130	135	0,315	0,760	-
335-0140-0000	140	145	0,295	0,820	-
335-0150-0000	150	155	0,275	0,880	5
335-0155-0000	155	160	0,265	0,900	5
335-0160-0000	160	165	0,255	0,930	-
335-0165-0000	165	170	0,250	0,960	5
335-0170-0000	170	175	0,240	0,990	-
335-0175-0000	175	180	0,235	1,020	-
335-0180-0000	180	185	0,230	1,050	5
335-0200-0000	200	205	0,205	1,140	5
335-0205-0000	205	210	0,200	1,190	5
335-0220-0000	220	225	0,185	1,280	-
335-0225-0000	225	230	0,180	1,310	-
335-0235-0000	235	240	0,175	1,360	-
335-0250-0000	250	255	0,165	1,450	5
335-0275-0000	275	280	0,150	1,590	5
335-0280-0000	280	285	0,145	1,620	-
335-0300-0000	300	305	0,135	1,730	-
335-0305-0000	305	310	0,135	1,770	5

### Contact us:

"DAIS GLOBAL " LTD  
3, Poruchik Nedelcho Bonchev Str., fl. 5  
1528 Sofia, Bulgaria  
Telephone: +359 2 973 27 67  
Fax: +359 2 973 26 65  
E-mail: office@daisglobal.eu

### Catalogues:

Ducting hoses  
Industrial hoses  
Fittings  
Safety couplings  
Chemical resistance table ducting hoses  
Chemical resistance table hoses



No	I.D. mm	O.D. mm	Pressure bar	Weight kg/m	Max length m
<b>335-0325-0000</b>	325	330	0,125	1,890	-
<b>335-0350-0000</b>	350	355	0,115	2,030	-
<b>335-0400-0000</b>	400	405	0,105	2,300	-
<b>335-0405-0000</b>	405	410	0,105	2,340	5
<b>335-0450-0000</b>	450	455	0,090	2,600	-
<b>335-0500-0000</b>	500	505	0,080	2,890	-
<b>335-0600-0000</b>	600	605	0,060	3,230	-

## Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5  
 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

## Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses