



PROTAPE® PUR-CU 335 MHF FLAT




Special and abrasion-proof hose,
especially suitable:

- for screening machines, vibrating screening machines and tumbler screening machines
- as bellows and compensator
- for the food and pharmaceutical industry

Hose construction

extruded tape; wall thickness 1.0 mm approx. wall: special premium ether-polyurethane (Pre-PUR®); smooth interior grounding wire



- vibration resistant
- highly flexible
- abrasion-proof
- smooth interior
- optimized flow properties

According to

- approved by an independent testing laboratory for the complete hose acc. to EU Directive 2002/72/EC, incl. amending Directive 975/2009 and Regulation No. 10/2011

Temperature range

-40°C ÷ +90°C, with peaks up to +125°C

| No | I.D. Mm/ | O.D. mm | Pressure bar | Weight kg/m |
|---------------|-------------|------------|-----------------|----------------|
| 335-0080-2878 | 80 | 85 | 0,860 | 0,520 |
| 335-0085-2878 | 85 | 90 | 0,800 | 0,560 |
| 335-0090-2878 | 90 | 95 | 0,770 | 0,600 |
| 335-0100-2878 | 100 | 105 | 0,690 | 0,660 |
| 335-0110-2878 | 110 | 115 | 0,630 | 0,730 |
| 335-0115-2878 | 115 | 120 | 0,605 | 0,750 |
| 335-0120-2878 | 120 | 125 | 0,580 | 0,790 |
| 335-0125-2878 | 125 | 130 | 0,560 | 0,820 |
| 335-0130-2878 | 130 | 135 | 0,535 | 0,860 |
| 335-0140-2878 | 140 | 145 | 0,500 | 0,930 |
| 335-0150-2878 | 150 | 155 | 0,460 | 1,000 |
| 335-0155-2878 | 155 | 160 | 0,440 | 1,020 |
| 335-0160-2878 | 160 | 165 | 0,435 | 1,060 |
| 335-0165-2878 | 165 | 170 | 0,420 | 1,090 |
| 335-0170-2878 | 170 | 175 | 0,410 | 1,130 |
| 335-0175-2878 | 175 | 180 | 0,400 | 1,160 |
| 335-0180-2878 | 180 | 185 | 0,385 | 1,200 |
| 335-0200-2878 | 200 | 205 | 0,350 | 1,310 |
| 335-0205-2878 | 205 | 210 | 0,345 | 1,370 |
| 335-0220-2878 | 220 | 225 | 0,320 | 1,470 |
| 335-0225-2878 | 225 | 230 | 0,310 | 1,500 |
| 335-0235-2878 | 235 | 240 | 0,295 | 1,570 |
| 335-0250-2878 | 250 | 255 | 0,280 | 1,680 |
| 335-0275-2878 | 275 | 280 | 0,255 | 1,840 |
| 335-0280-2878 | 280 | 285 | 0,250 | 1,880 |

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5
1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses



| No | I.D. Mm/ | O.D. mm | Pressure bar | Weight kg/m |
|----------------------|-------------|------------|-----------------|----------------|
| 335-0300-2878 | 300 | 305 | 0,230 | 2,010 |
| 335-0305-2878 | 305 | 310 | 0,230 | 2,060 |
| 335-0325-2878 | 325 | 330 | 0,215 | 2,160 |
| 335-0350-2878 | 350 | 355 | 0,200 | 2,310 |
| 335-0400-2878 | 400 | 405 | 0,170 | 2,660 |
| 335-0405-2878 | 405 | 410 | 0,170 | 2,740 |
| 335-0450-2878 | 450 | 455 | 0,155 | 2,960 |
| 335-0500-2878 | 500 | 505 | 0,140 | 3,220 |
| 335-0600-2878 | 600 | 605 | 0,110 | 3,800 |

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5
1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses