



PROTAPE® PVC 371




Suction and blast hose, especially suitable:

- for welding gas extraction
- for air conditioning and ventilation technique

Hose construction

1. spring steel wire integrated in wall
2. fabric-reinforced tape wall: PVC coated fabric
3. wall thickness 0.25 mm approx.



Temperature range

-10°C ÷ +80°C



- super-light model
- highly flexible + compressible 6:1
- fabric reinforced
- good resistance to alkalis and acids
- good resistance to chemicals
- good resistance to UV and ozone
- small bending radius

According to

- German TRBS 2153 (formerly BGR 132): capable of electro-static discharge by grounding the spiral

No	I.D. mm	O.D. mm	Pressure bar	Vacuum bar	Bend radius mm	Weight kg/m	Max length m
371-0040-0000	40	43	0,250	0,150	43	0,100	6 10
371-0051-0000	51	54	0,240	0,145	54	0,120	6 10
371-0060-0000	60	63	0,195	0,115	63	0,140	6 10
371-0076-0000	76	79	0,160	0,080	79	0,180	6 10
371-0080-0000	80	83	0,150	0,070	83	0,190	6 10
371-0090-0000	90	93	0,140	0,060	93	0,200	6 10
371-0102-0000	102	105	0,120	0,050	105	0,240	6 10
371-0110-0000	110	113	0,110	0,045	113	0,270	6 10
371-0127-0000	127	130	0,100	0,035	130	0,320	6 10
371-0140-0000	140	143	0,090	0,035	143	0,350	6 10
371-0152-0000	152	155	0,080	0,035	155	0,370	6 10
371-0160-0000	160	163	0,075	0,025	163	0,440	6 10
371-0180-0000	180	183	0,070	0,020	183	0,540	6 10
371-0203-0000	203	206	0,060	0,020	206	0,600	6 10
371-0254-0000	254	258	0,050	0,010	258	0,790	6 10
371-0305-0000	305	309	0,040	0,005	309	0,950	6 10
371-0356-0000	356	360	0,035	0,005	360	1,110	6 10
371-0406-0000	406	410	0,030	0,005	410	1,280	6 10
371-0508-0000	508	514	0,020	0,002	514	1,560	6 10
371-0040-0001	40	43	0,250	0,150	43	0,100	6 10
371-0051-0001	51	54	0,240	0,145	54	0,120	6 10
371-0060-0001	60	63	0,195	0,115	63	0,140	6 10
371-0076-0001	76	79	0,160	0,080	79	0,180	6 10
371-0080-0001	80	83	0,150	0,070	83	0,190	6 10
371-0090-0001	90	93	0,140	0,060	93	0,200	6 10

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses



No	I.D. mm	O.D. mm	Pressure bar	Vacuum bar	Bend radius mm	Weight kg/m	Max length m
371-0102-0001	102	105	0,120	0,050	105	0,240	6 10
371-0110-0001	110	113	0,110	0,045	113	0,270	6 10
371-0127-0001	127	130	0,100	0,035	130	0,320	6 10
371-0140-0001	140	143	0,090	0,035	143	0,320	6 10

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5
1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses