



PYTHON N/L 20

Designed for air, cold and hot water and light-chemical media. Major properties of PYTHON hoses are:

- high ozone resistance
- antistatic resistance
- high temperature resistance
- low temperature resistance
- non-staining cover
- high flexibility

Hose construction

Tube: Black, antistatic (R<10 6 /m), smooth EPDM nitrosamine free rubber compound, resistant to lightchemical media

Reinforcement: Synthetic textile yarns

Cover: Black, antistatic (R<10 6 /m), smooth EPDM nitrosamine free rubber compound



- Antistatic tube and cover suitable for Atex applications
- Unmatchable handiness
- Wide range temperature
- Its versatility of use helps to keep a controlled stock
- Nitrosamine free
- Burst Pressure Value 3:1

According to

I.D. ≤ 25 mm UNI EN ISO 1307

I.D. > 25 mm RMA steel mandrel

Temperature range

-40°C ÷ +120°C with peaks to +140°C

Number	I.D.	O.D.	WP	BP	W	R min
	mm	mm	bar	bar	kg	mm
IH30351270/40	10	17	20	60	0.22	60
IH30351271/40	13	20	20	60	0.26	80
IH30351272/40	15	22	20	60	0.29	90
IH30351273/40	19	27	20	60	0.41	110
IH30351274/40	25	34	20	60	0.60	150
IH36351270/40	32	44	20	60	0.98	320
IH36351271/40	38	51	20	60	1.20	380
IH36351272/40	50	66	20	60	1.76	500

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses