



## RADIOR 10

Flexible rubber hose for delivery of hot water in heating and cooling of automotive LPG and methane systems.

### Hose construction

**Tube:** Black, smooth EPDM nitrosamine free rubber compound

**Reinforcement:** Synthetic textile yarns

**Cover:** Smooth, black, heat, ageing and weather-resistant EPDM nitrosamine free rubber compound

### Temperature Range

-30 °C to + 100 °C, with peaks +120 °C

### Tolerances

I.D. : ± 0,80 mm

L. : ± 1%



- Specific for cooling system
- Also used in combination with Autogas ECE 67/110 in CNG/LPG engines
- Robust structure to avoid kinking
- Burst Pressure Value 3:1

### According to

UNI EN ISO 1307/97

Number	ID mm	OD mm	WP bar	BP bar	Weight kg	R min mm
IH30114029/100	7	13	10	30	0.13	50
IH30114030/50	15	23	10	30	0.35	90
IH30114030/100	15	23	10	30	0.35	90

## Contact us:

"DAIS GLOBAL " LTD

3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria

Telephone: +359 2 973 27 67

Fax: +359 2 973 26 65

E-mail: office@daisglobal.eu

## Catalogues:

Ducting hoses

Industrial hoses

Fittings

Safety couplings

Chemical resistance table ducting hoses

Chemical resistance table hoses