



RADIOR 3

Designed for cooling systems of automotive engines and stationary engines.

Hose construction

Tube: Black, smooth, heat resistant EPDM nitrosamine free rubber compound

Reinforcement: Synthetic textile yarn fabric

Cover: Black, smooth, heat, ageing and weather-resistant EPDM nitrosamine free rubber compound

Temperature range

-40 °C to +100 °C

Tolerances

I.D. ≤ 22 mm according to UNI EN ISO 1307

O.D. > 22 mm according to RMA steel mandrel



- Light and exible hose
- Also suitable as cable protection
- Nitrosamine free
- Burst Pressure Value 3:1

According to

UNI EN ISO 1307, RMA steel mandrel

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	Min R mm
IH36830095/40	10	16	3	9	0,16	-
IH36830096/40	12	18	3	9	0,19	-
IH36830097/40	15	21	3	9	0,23	-
IH36830101/40	18	24,5	3	9	0,29	-
IH36830102/40	20	26,5	3	9	0,32	-
IH36830103/40	22	28,5	3	9	0,34	-
IH36830104/40	25	32	3	9	0,39	-
IH36830105/40	28	36	3	9	0,50	-
IH36830106/40	30	38	3	9	0,53	-
IH36830107/40	32	40	3	9	0,55	-
IH36830108/40	35	43	3	9	0,60	-
IH36830109/40	38	47	3	9	0,73	-
IH36830110/40	40	49	3	9	0,77	-
IH36830111/40	42	51	3	9	0,80	-
IH36830112/40	45	54	3	9	0,85	-
IH36831023/40	48	57	3	9	0,91	-
IH36830113/40	50	60	3	9	1,07	-
IH36830114/40	55	65	3	9	1,17	-
IH36830115/40	60	70	3	9	1,26	-
IH36830116/20	65	76	3	9	1,54	-
IH36830117/20	70	81	3	9	1,65	-
IH36831022/20	75	86	3	9	1,75	-
IH36830118/20	80	92	3	9	2,05	-
IH36830119/20	90	102	3	9	2,29	-
IH36830120/20	100	113	3	9	2,63	-

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses