



## RAGUSA 4

Suitable for suction and delivery of mineral oils and fuels having an aromatic content not exceeding 50 %, when a lightweight and flexible hose is required.

### Hose construction

**Tube:** Black, smooth, NBR rubber compound, resistant to oil and fuel with an aromatic content not exceeding 50 %

**Reinforcement:** Synthetic textile fabrics, rembedded steel wire helix and built-in copper wire for electrical continuity at both ends

**Cover:** Black, oil, fuel, abrasion and weather resistant, antistatic ( $R < 1 \text{ M/m}$ ) corrugated NBR/SBR rubber compound. Generally manufactured with soft cu-ed ends and supplied in lengths required

### Temperature range°

-25°C ÷ + 80°C, to 100°C for oil



- Very low bending radius
- Customized length
- Soft cu-ed ends for clamps fixing
- Burst Pressure Value 4:1

**According to**  
RMA steel mandrel

Number	ID mm	OD mm	WP bar	BP bar	Weight kg	R мин mm
IH36538099/0	38	-	4	16	1.10	150
IH36538100/0	40	-	4	16	1.15	160
IH36538101/0	50	-	4	16	1.39	200
IH36538106/0	60	-	4	16	1.80	240
IH36538105/0	63.5	-	4	16	1.89	250
IH36538102/0	75	-	4	16	2.19	300
IH36538103/0	80	-	4	16	2.32	320
IH36538104/0	100	-	4	16	3.08	400

## Contact us:

"DAIS GLOBAL " LTD  
3, Poruchik Nedelcho Bonchev Str., fl. 5  
1528 Sofia, Bulgaria  
Telephone: +359 2 973 27 67  
Fax: +359 2 973 26 65  
E-mail: office@daisglobal.eu

## Catalogues:

Ducting hoses  
Industrial hoses  
Fittings  
Safety couplings  
Chemical resistance table ducting hoses  
Chemical resistance table hoses