



## ROBUR GPL

Liquid gas applications (methane, propane, LPG) in the loading and unloading of tankers and in the service stations.

### Hose construction

**Tube:** Low diusion rate seamless extruded NBR rubber compound of uniform thickness.

**Reinforcement:** Two braids of high tensile steel wire

**Cover:** Black, SBR/CR rubber compound pin-pricked to prevent the formation of blisters, resistant to abrasion, oils, ozone and weathering.



- Suitable for vacuum application
- Low permeability
- Pin-pricked cover
- Burst Pressure Value 10:1

### Temperature range°

-30°C to +70°C

### Tolerances

Length tolerance  $\pm 1 \%$

Number	ID mm	OD mm	WP bar	BP bar	Weight kg	R мин mm
IH36520560/0	6,5	16,6	25	1380	0,43	60
IH36520561/0	8	17,7	25	1180	0,45	70
IH36520562/0	9,5	20,2	25	1100	0,56	80
IH36520563/0	13	23,2	25	960	0,68	90
IH36520564/0	16	26,5	25	760	0,80	95
IH36520565/0	19	30,5	25	620	1,03	100
IH36520566/0	25	38,5	25	560	1,41	150
IH36520567/0	32	45,6	25	440	1,82	200
IH36520568/0	38	52	25	340	2,00	280
IH36520569/0	51	66,5	25	320	2,86	350

## Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5  
 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

## Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses