

SHANNON 80 HD

Steel cord hose used for concrete placement at casting locations; it is used at the end of the pumps to distribute the concrete. The hose resists suction during the cleaning process. Usually supplied with swaged on "Full flow" hardened couplings.

Hose construction

Tube: black, smooth, NR/SBR rubber, that withstands the abrasive action of the concrete.

Reinforcement: plies of steel wire cord.

Cover: black, smooth (wrapped finish), NR/SBR rubber, abrasion and weathering resistant.



- Rubber, concrete placement hose
- Antistatic
- Working pressure 85bar
- Vacuum 0,8bar

Temperature range

-40°C to +70°C

Number	ID mm	OD mm	WP bar	Burst pressure bar	Weight kg/m	Bending radius mm	Vacuum bar	Max length m
IH36827051	51	71,5	85	200	3,38	380	0,8	60
IH36827052	65	89	85	200	4,72	400	0,8	60
1451715	65	85	85	200	4,11	400	0,8	60
1443666	76	97	85	200	4,92	400	0,8	60
IH36827053	76	100	85	200	5,42	400	0,8	60
IH36827054	100	124	85	200	6,87	550	0,8	60
1443658	102	123	85	200	6,39	550	0,8	60
IH36827055	125	150	85	200	8,69	700	0,8	60
1443640	127	150	85	200	8,24	700	0,8	60
1452649	152	181	85	200	13,28	840	0,8	60

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses