



SLIMLINE

Quality petrol pump hoses for gasoline and diesel fuels. Also suitable for fuels with ethanol content up to E 85.
Can be calibrated for electric dispensing pumps, see overleaf.

Hose construction

Lining: Nitrile rubber (NBR), conductive, no discolouration

Reinforcements: Two low tensile textile braids with crossed, interwoven conductivity strands

Cover: Resistant to light cracks and oil. Material see chart

Temperature range°

-30°C to +55°C



- Suitable for cold and warm regions.
- Due to the smooth cover and high flexibility, all Slimline hoses are perfectly suitable for MPD hose retraction systems.

According to
EN 1360

Number	ID mm	OD mm	WP bar	BP bar	Weight kg	R мин mm
SL16/40÷80	16	26	16	64	0,5	80
SL19/40÷80	19	30	16	64	0,55	90
SL21/40÷80	21	31	16	64	0,55	100
SL25/40÷80	25	36	16	64	0,8	150

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5
1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses