



SuperFlex PVC 372




Suction and blast hose, especially suitable:

- for solids such as dust, powder and fibres
- for gaseous and liquid media
- for domestic and industrial vacuum cleaners, building drying, welding gas extraction

Hose construction

plastic coated spring steel wire
fabric-reinforced tape
wall: high grade soft PVC



Temperature range

0 °C ÷ +85 °C



- fibre reinforced
- good resistance to alkalis and acids
- good resistance to chemicals
- good resistance to UV and ozone
- small bending radius

According to

- German TRBS 2153 (formerly BGR 132): capable of electro-static discharge by grounding the spiral

No	I.D. mm	O.D. mm	Pressure bar	Vacuum bar	Bend radius mm	Weight kg/m	Max length m
372-0025-0000	25	31	1,700	0,200	25	0,200	15
372-0028-0000	28	34	1,600	0,200	28	0,230	15
372-0032-0000	32	38	1,500	0,200	32	0,280	15
372-0035-0000	35	41	1,400	0,200	35	0,310	15
372-0038-0000	38	44	1,400	0,200	38	0,340	15
372-0041-0000	41	47	1,400	0,180	41	0,370	15
372-0044-0000	44	50	1,300	0,160	44	0,380	15
372-0051-0000	51	57	1,300	0,150	51	0,460	15
372-0063-0000	63	69	1,000	0,140	62	0,530	15
372-0070-0000	70	76	0,900	0,120	70	0,580	10
372-0076-0000	76	82	0,800	0,100	76	0,680	10
372-0080-0000	80	86	0,700	0,090	80	0,830	10
372-0089-0000	89	95	0,700	0,090	89	0,930	10
372-0100-0000	100	106	0,600	0,080	102	1,000	10

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5
1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses