

SUPERTOP UPE COND LL

Hardwall smooth hose to convey a wide range of aggressive chemicals, solvents, petroleum products and oils. Hose tested and approved by INERIS for use in ATEX areas. Normally installed on tank trucks and discharge platforms in chemical and oil industries.

Hose construction

Tube: black, smooth, high weight cross-linked polyethylene (UPE). Chemical resistance according to IVG chemical resistance chart. For temperature exceeding 50°C contact IVG.

Reinforcement: high strength synthetic cord and steel helix wire.

Cover: black, smooth (wrapped finish), EPDM rubber, resistant to chemicals, abrasion, weathering and ozone.

Temperature range

-40°C to +100°C



- Conductive hose to convey chemicals and petroleum products, with UPE tube. Approved for use in ATEX areas.
- Working pressure 16bar
- According to EN 12115: 11, EN 13463-1 / EN 60079-0.

Number	ID mm	OD mm	WP bar	Burst pressure bar	Weight kg/m	Bending radius mm	Vacuum bar	Max lenght m
IH36811529	19	31	16	64	0,70	90	0,9	60
IH36811530	25	38	16	64	0,90	120	0,9	60
IH36811531	32	44	16	64	1,04	150	0,9	60
IH36811532	38	51	16	64	1,35	180	0,9	60
IH36811534	51	65	16	64	1,79	280	0,9	60
IH36811535	63,5	78	16	64	2,34	320	0,9	60
IH36811536	75	90	16	64	2,81	400	0,9	60
IH36811538	102	118	16	64	4,32	550	0,9	60

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses