

SUPERTOP UPE

Softwall hose suitable for handling a wide range of aggressive chemicals, solvents, alcohols and food. Normally installed on tank trucks and discharge platforms in chemical, oil and food industries.

Hose construction

Tube: white, food quality, smooth, high weight cross-linked polyethylene (UPE). Chemical resistance according to IVG chemical resistance chart.

Reinforcement: high strength synthetic cord and antistatic copper wire.

Cover: green, smooth (wrapped finish), EPDM rubber resistant to chemicals, abrasion, weathering and ozone.

Temperature range

-40°C to +100°C



- Flexible hose for delivery of aggressive chemicals, solvents, alcohols and food, with UPE tube. Phthalates free.
- Electrical resistance
- Working pressure 16bar
- According to EN 12115: 11 . Tube: Per. CE 1935/04 и CE 2023/06.

Number	ID mm	OD mm	WP bar	Burst pressure bar	Weight kg/m	Max lenght m
IH36811590	19	31	16	64	0,53	60
IH36811591	25	37	16	64	0,66	60
IH36811592	32	45	16	64	0,85	60
IH36811593	38	52	16	64	1,09	60
IH36811594	51	67	16	64	1,61	60
IH36811595	63,5	79	16	64	1,90	60
IH36811596	76	92	16	64	2,33	60
IH36811597	102	118	16	64	2,94	60

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses