



TBSE

Desigend for general applications in fuel systems where low permeability levels are required. Suitable for leaded and unleaded fuels and diesel.

Hose construction

Tube: Black, oil and fuel resistant, smooth, antistatic (R < 1 M/m), NBR rubber compound

Reinforcement: Synthetic textile yarns

Cover: Black, oil, fuel, abrasion, eatherresistant, smooth, antistatic (R < 1 M/m), NBR/EPDM rubber compound.



- Antistatic cover and tube compounds
- Low permeability
- Suitable for B20 and E100 up to 70 °C
- Available packaging in reels for display stand
- Burst Pressure Value 3:1

Temperature Range

-30°C ÷ +100°C

Tolerances

I.D. ≤ 5 mm: ± 0,6
> 5 mm: ± 0,8

L ± 1%

According to

UNI EN ISO 1307/97

Number	ID mm	OD mm	WP bar	BP bar	Weight kg	R min mm
IH30871001/100	4	9	10	30	0.07	30
IH30871011/100	5	10	10	30	0.08	40
IH30871021/100	6	13	10	30	0.14	55
IH30871031/100	7	13	10	30	0.13	55
IH30871041/100	7.5	14	10	30	0.15	65
IH30871051/100	10	16	10	30	0.17	75

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses