



THERMOPRESS 10

Suitable for delivery of hot water, non-aggressive hot liquids and steam to a maximum temperature of +120 °C (+248 °F). To connect boilers to air conditioning units and for hot water cleaning systems.

Hose construction

Tube: Black, smooth, heat resistant, EPDM nitrosamine free rubber compound

Reinforcement: Synthetic textile fabrics or yarns

Cover: Black, smooth, heat, ageing and weather-resistant EPDM nitrosamine free rubber compound

Temperature range

-40 °C ÷ +100 °C, peaks up to +120 °C

Tolerances

I.D. ≤ 22 mm according to UNI EN ISO 1307

O.D. > 22 mm according to RMA steel mandrel



- Robust structure
- Wide temperature range
- Nitrosamine free
- Burst Pressure Value 4:1

According to

UNI EN ISO 1307, RMA steel mandrel

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	Min R mm
IH36800002/100	12	22,5	10	40	0,38	120
IH36800003/80	15	25,5	10	40	0,44	150
IH36800004/80	18	28,5	10	40	0,51	180
IH36800005/80	20	30,5	10	40	0,56	200
IH36800006/40	25	35	10	40	0,61	250
IH36800007/40	30	41	10	40	0,79	300
IH36800009/40	40	54	10	40	1,34	400
IH36800011/40	50	68	10	40	2,12	500
IH36800012/40	60	82	10	40	3,10	600

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses