



## TIMBERDUC® PUR 532 SE




Special suction and blast hose in flame-retardant polyurethane resistant to aggressive wood types and wood preservatives, especially suitable:

- for the suction of wood dust and wood chips on wood processing machines
- for abrasive solids such as dust, powder, fibres and chips
- for de-dusting and suction plants

### Hose construction

1. spring steel wire integrated in wall
2. extruded tape wall: premium polyurethane, resistant to aggressive wood types and wood preservatives, with flame-retardant additive (Pre-PUR®)
3. wall thickness 0.6 mm approx.



- optimized flow properties
- high tensile strength and tear resistant
- microbe and hydrolysis resistant
- good resistance to mineral oils and gasoline

### According to

- German TRBS 2153 (formerly BGR 132): capable of electro-static discharge by grounding the spiral

### Temperature range

-40°C ÷ +90°C, with peaks up to +125°C

No	I.D. mm	O.D. mm	Vacuum bar	Bend radius mm	Weight kg/m	Max length m
532-0040-0000	40	47	0,300	47	0,260	10
532-0045-0000	45	52	0,285	52	0,290	-
532-0050-0000	50	58	0,260	58	0,360	10
532-0055-0000	55	63	0,240	63	0,390	-
532-0060-0000	60	68	0,210	68	0,430	10 15
532-0063-0000	63	71	0,195	71	0,450	-
532-0065-0000	65	73	0,180	73	0,470	10
532-0070-0000	70	78	0,150	78	0,500	10
532-0075-0000	75	83	0,140	83	0,530	10
532-0080-0000	80	88	0,130	88	0,570	10 15
532-0090-0000	90	98	0,115	98	0,630	10
532-0100-0000	100	108	0,090	108	0,660	10 15
532-0110-0000	110	118	0,080	118	0,730	10
532-0115-0000	115	123	0,080	123	0,760	-
532-0120-0000	120	128	0,075	128	0,790	10 15
532-0125-0000	125	133	0,060	133	0,820	10 15
532-0130-0000	130	138	0,060	138	0,850	10

### Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5  
 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

### Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses



No	I.D. mm	O.D. mm	Vacuum bar	Bend radius mm	Weight kg/m	Max length m
<b>532-0140-0000</b>	140	148	0,060	148	0,920	<b>10 15</b>
<b>532-0150-0000</b>	150	158	0,055	158	0,980	<b>10 15</b>
<b>532-0160-0000</b>	160	168	0,050	168	1,040	<b>10 15</b>
<b>532-0170-0000</b>	170	178	0,045	178	1,110	-
<b>532-0175-0000</b>	175	183	0,040	183	1,140	-
<b>532-0180-0000</b>	180	188	0,040	188	1,170	<b>10 15</b>
<b>532-0200-0000</b>	200	208	0,040	208	1,540	<b>10 15</b>
<b>532-0225-0000</b>	225	233	0,030	233	1,750	<b>10</b>
<b>532-0250-0000</b>	250	258	0,015	258	1,900	<b>10</b>
<b>532-0275-0000</b>	275	283	0,015	283	2,110	-
<b>532-0280-0000</b>	280	288	0,015	288	2,150	<b>10</b>

## Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5  
 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

## Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses